

Application No. 10/657,512
Amendment dated MAY 9, 2005
Reply to Office Action dated February 9, 2005

Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims

1 – 33. (Canceled)

34. (Currently amended) A method of creating a groove in a surface of a collector ring of an electrical device, the method comprising:

cutting the groove in the surface of the collector ring using a ~~cutting tool that has a cutting action that functions independently from the motion of the collector ring~~ hand held rotary grinder.

35. (Previously presented) The method of claim 34, wherein the collector ring remains coupled to at least a portion of the electrical device when creating the groove in the surface of the collector ring.

36. (Previously presented) The method of claim 34, wherein the electrical device comprises a large industrial generator.

37. (Previously presented) The method of claim 34, wherein the electrical device comprises an industrial power plant generator.

38. (Previously presented) The method of claim 34, wherein the electrical device comprises an electrical motor.

39-43. (Cancelled)

44. (Previously presented) The method of claim 34, wherein the groove that is created is a helical shaped groove about the surface of the collector ring.

Application No. 10/657,512

Amendment dated MAY 9, 2005

Reply to Office Action dated February 9, 2005

45. (Previously presented) The method of claim 34, wherein the collector ring is cylindrical in shape, and the surface is an outer peripheral surface, and the groove forms a helical or spiral shape about the outer peripheral surface of the cylindrical collector ring.

46. (Currently amended) A method of creating a groove in a surface of a collector ring for use in an industrial power plant generator, the method comprising:

cutting the groove in the surface of the collector ring using a ~~cutting tool that has a cutting action that functions independently from the motion of the collector ring~~ hand held rotary grinder, wherein the collector ring remains coupled to at least a portion of the electrical generator when creating the groove in the surface of the collector ring.

47-50. (Cancelled)

51. (Previously presented) The method of claim 46, wherein the groove that is created is a helical shaped groove about the surface of the collector ring.

52. (Previously presented) The method of claim 46, wherein the collector ring is cylindrical in shape, and the surface is an outer peripheral surface, and the groove forms a helical or spiral shape about the outer peripheral surface of the cylindrical collector ring.

53. (Currently amended) A method for creating a groove in a peripheral surface of a collector ring of an electrical generator, the method comprising:

providing a means for cutting, ~~the means for cutting being hand held having a cutting action that functions independently from the motion of the collector ring;~~ and

cutting the groove in the peripheral surface of the collector ring using the cutting means.

54. (New) The method of claim 34, wherein the groove is not present before the method is performed.

Application No. 10/657,512

Amendment dated MAY 9, 2005

Reply to Office Action dated February 9, 2005

55. (New) The method of claim 34, wherein the groove has a first depth before the method is performed and a second depth after the method is performed and wherein the second depth is greater than the first depth.

56. (New) The method of claim 55, wherein the second depth is substantially greater than the first depth.

57. (New) The method of claim 46, wherein the groove is not present before the method is performed.

58. (New) The method of claim 46, wherein the groove has a first depth before the method is performed and a second depth after the method is performed and wherein the second depth is greater than the first depth.

59. (New) The method of claim 58, wherein the second depth is substantially greater than the first depth.

60. (New) A method of creating a groove in a surface of a collector ring of an electrical device, the method comprising:

cutting the groove in the surface of the collector ring using a cutting tool that has a cutting action that functions independently from the motion of the collector ring;

wherein the groove is not present before the method is performed.

61. (New) A method of creating a groove in a surface of a collector ring of an electrical device, the method comprising:

cutting the groove in the surface of the collector ring using a cutting tool that has a cutting action that functions independently from the motion of the collector ring;

wherein the groove has a first depth before the method is performed and a second depth after the method is performed and wherein the second depth is greater than the first depth.

Application No. 10/657,512
Amendment dated MAY 9, 2005
Reply to Office Action dated February 9, 2005

62. (New) The method of claim 61, wherein the second depth is substantially greater than the first depth.